

Hitachi Block Storage Driver for Red Hat OpenStack Platform

Driver Migration Guide

This guide provides information about migration from Hitachi Block Storage Driver version 9.0 to Red Hat OpenStack Platform 16.2 intree driver.

MK-92ADPTR159-00

August 2023

(c) 2023 Hitachi Vantara LLC. All rights reserved.

No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or stored in a database or retrieval system for commercial purposes without the express written permission of Hitachi, Ltd., or Hitachi Vantara Corporation (collectively, "Hitachi"). Licensee may make copies of the Materials provided that any such copy is: (i) created as an essential step in utilization of the Software as licensed and is used in no other manner; or (ii) used for archival purposes. Licensee may not make any other copies of the Materials. "Materials" mean text, data, photographs, graphics, audio, video and documents.

Hitachi reserves the right to make changes to this Material at any time without notice and assumes no responsibility for its use. The Materials contain the most current information available at the time of publication.

Some of the features described in the Materials might not be currently available. Refer to the most recent product announcement for information about feature and product availability, or contact Hitachi Vantara Corporation at https://support.HitachiVantara.com/en_us/contact-us.html.

Notice: Hitachi products and services can be ordered only under the terms and conditions of the applicable Hitachi agreements. The use of Hitachi products is governed by the terms of your agreements with Hitachi Vantara Corporation.

By using this software, you agree that you are responsible for:

- 1) Acquiring the relevant consents as may be required under local privacy laws or otherwise from authorized employees and other individuals to access relevant data; and
- 2) Verifying that data continues to be held, retrieved, deleted, or otherwise processed in accordance with relevant laws.

Notice on Export Controls. The technical data and technology inherent in this Document may be subject to U.S. export control laws, including the U.S. Export Administration Act and its associated regulations, and may be subject to export or import regulations in other countries. Reader agrees to comply strictly with all such regulations and acknowledges that Reader has the responsibility to obtain licenses to export, re-export, or import the Document and any Compliant Products.

EXPORT CONTROLS - Licensee will comply fully with all applicable export laws and regulations of the United States and other countries, and Licensee shall not export, or allow the export or re-export of, the Software, API, or Materials in violation of any such laws or regulations. By downloading or using the Software, API, or Materials, Licensee agrees to the foregoing and represents and warrants that Licensee is not located in, under the control of, or a national or resident of any embargoed or restricted country.

Hitachi is a registered trademark of Hitachi, Ltd., in the United States and other countries.

AIX, AS/400e, DB2, Domino, DS6000, DS8000, Enterprise Storage Server, eServer, FICON, Flash Copy, IBM, Lotus, MVS, OS/390, PowerPC, RS6000, S/390, System z9, System z10, Tivoli, z/OS, z9, z10, z13, z/VM, BCPII™ and z/VSE are registered trademarks or trademarks of International Business Machines Corporation.

Active Directory, ActiveX, Bing, Excel, Hyper-V, Internet Explorer, the Internet Explorer logo, Microsoft, the Microsoft Corporate Logo, MS-DOS, Outlook, PowerPoint, SharePoint, Silverlight, SmartScreen, SQL Server, Visual Basic, Visual C++, Visual Studio, Windows, the Windows logo, Windows Azure, Windows PowerShell, Windows Server, the Windows start button, and Windows Vista are registered trademarks or trademarks of Microsoft Corporation. Microsoft product screen shots are reprinted with permission from Microsoft Corporation.

All other trademarks, service marks, and company names in this document or web site are properties of their respective owners.

Table of Contents

Preface	4
About this document.....	4
Document conventions.....	4
Intended audience.....	4
Scope of this document	5
Preparation for migration	5
Overview of differences in Cinder driver	5
Known issue in migrating	10
Operation for migration	11
Backing up configuration files	11
Updating RHOSP	12
Installing Driver.....	12
Fixing configuration files.....	13
Migrating Driver	14
Operation differences after migration	14
Restrictions	14
Known Issues	14

Preface

About this document

This document provides technical information and procedures for migration from Red Hat OpenStack Platform("RHOSP") 16.1 with Hitachi Block Storage Driver("HBSD") to RHOSP 16.2 intree driver.

Document conventions

This document uses the following typographic convention:

Convention	Description
Bold	<ul style="list-style-type: none">Indicates text in a window, including window titles, menus, menu options, buttons, fields, and labels. Example: Click OK.Indicates emphasized words in list items.
<i>Italic</i>	Indicates a document title or emphasized words in text.
Monospace	Indicates text that is displayed on screen or entered by the user. Example: <code>pairdisplay -g oradb</code>

Intended audience

This document is intended for operators and administrators who configure and operate cloud systems using Red Hat OpenStack Platform.

This document assumes basic knowledge of Linux operating systems.

Scope of this document

This document shows settings and operations for Cinder driver when migrating from RHOSP16.1 to RHOSP16.2. About updating RHOSP, refer the document [Keeping Red Hat OpenStack Platform Updated](#), which is provided by Red Hat.

Preparation for migration

Overview of differences in Cinder driver

Type of Cinder driver

Two types of Cinder driver for RHOSP are existing, out of tree driver and intree driver. Only intree driver can get Red Hat driver certification. For Hitachi block storages, only intree driver will be provided for RHOSP 16.2 or later. Hitachi has got Red Hat driver certification for RHOSP16.2 intree driver.

Items	RHOSP16.1	RHOSP 16.2 or later
Provided driver type	Out of tree driver	Intree driver
Provided by	Hitachi	Red Hat
How to get the driver	Download from the vender site	Including in RHOSP package
Customer support	Hitachi	Red Hat

Supported features

Supported features are different among the out of tree driver, the intree driver and the patched intree driver. See the following table:

#	Feature	RHOSP16.1 Out of tree(v9.0)	RHOSP16.2 intree
1	Required features: <ul style="list-style-type: none"> • Create, delete, attach, and detach volumes. • Create, list, and delete volume snapshots. • Create a volume from a snapshot. • Create, list, update, and delete consistency groups. • Create, list, and delete consistency group snapshots • Copy a volume to an image • Copy an image to a volume • Clone a volume • Extend a volume • Migrate a volume(host assisted) • Get volume statistics. • Efficient non-disruptive volume backup • Manage and unmanage a volume • Attach a volume to multiple instances at once (multi-attach) • Revert a volume to a snapshot 	Y	Y
2	Multipath	Y	Y
3	Live migration	Y	Y
4	Consistency groups	Y	N/A
5	Global-active device	Y	N/A
6	Remote replication	Y ¹	N/A
7	QoS	Y	N/A
8	Multi pools	Y	N/A
9	Deduplication and compression	Y	N/A
10	Storage assisted migration	N/A	N/A

11	Port assignment using extra spec	Y	N/A
12	Port scheduler	Y	N/A
13	REST API server on the management server	Y	Y
14	REST API server on the storage	N/A	Y
15	REST API server on Hitachi Storage Advisor Embedded	Y	N/A
16	Copy method for old storage model	Y	N/A
17	hbsdgetinfo command	Y	N/A
18	High Availability(Active-Standby)	Y	Y
19	High Availability(Active-Active)	N/A	N/A

Legend:

- Y: Supported
- N/A: Not Available

Note:

1. Supported as "tech-preview" because RedHat supports this feature as tech-preview

Driver name

Driver name is different between out of tree driver and intree driver. Fix cinder.conf along the following table, when migration.

Driver type	Driver name ¹	
	RHOSP16.1 Out of tree(v9.0)	RHOSP16.2 intree
Fibre Channel	cinder.volume.drivers.hitachi. hbsd.hbsd_fc .HBSDFCDriver	cinder.volume.drivers.hitachi. hbsd_fc .HBSDFCDriver
iSCSI	cinder.volume.drivers.hitachi. hbsd.hbsd_iscsi .HBSDISCSIDriver	cinder.volume.drivers.hitachi. hbsd_iscsi .HBSDISCSIDriver

Note:

1. Driver name is set as a value of the parameter "volume_driver" in cinder.conf)

Parameters and default values

Support parameter, parameter names and default value of parameters are different between the out of tree driver and intree driver. Fix cinder.conf along the following table, when migration.

Parameter name		Default value	
RHOSP16.1 Out of tree(v9.0)	RHOSP16.2 intree	Out of tree	Intree
hitachi_storage_id		None	None
hitachi_storage_cli	-	REST	N/A (Work as REST)
hitachi_ldev_range		None	None
hitachi_pool		None	None
hitachi_target_port		[]	[]
hitachi_compute_target_port		[]	[]
hitachi_thin_pool	hitathi_snap_pool	None	None
hitachi_rest_number	hitachi_replication_number	0	N/A
hitachi_rest_user	san_login	None	None
hitachi_rest_password	san_password	None	None
hitachi_rest_password_path	-	None	N/A
hitachi_rest_tcp_keepalive		True	True
hitachi_rest_name_only_discovery	-	False	N/A
hitachi_rest_pair_target_ports		[]	[]
hitachi_group_request	hitachi_group_create	False	False
hitachi_use_chap_auth	-	False	N/A
hitachi_auth_user	chap_username	None	None
hitachi_auth_password	chap_password	None	None
hitachi_auth_password_path	-	None	N/A
hitachi_copy_version	-	2.0	N/A (Work as 2.0)
hitachi_default_copy_method	-	FULL	N/A (Work as FULL for copy, THIN for snapshot)
hitachi_copy_speed		3	N/A
hitachi_copy_check_interval		3	N/A
hitachi_async_copy_check_interval		10	N/A
hitachi_rest_disable_io_wait		False	N/A
hitachi_rest_api_ip	san_ip	""	""
hitachi_rest_api_port	san_api_port	23451	443
hitachi_over_subscription	-	False	N/A

			(Work as True)
hitachi_server_auto_create	-	True	N/A
hitachi_server_auto_delete	-	False	N/A
hitachi_pair_target_number		0	0
hitachi_discard_zero_page		True	True
hitachi_host_mode_options		None	[]
hitachi_gad_auth_password	-	None	N/A
hitachi_gad_auth_password_path	-	None	N/A
hitachi_gad_auth_user	-	None	N/A
hitachi_gad_compute_target_ports	-	[]	N/A
hitachi_gad_ldev_range	-	None	N/A
hitachi_gad_path_group_id	-	0	N/A
hitachi_gad_pool	-	None	N/A
hitachi_gad_rest_api_ip	-	""	N/A
hitachi_gad_rest_api_port	-	23451	N/A
hitachi_gad_rest_pair_target_ports	-	[]	N/A
hitachi_gad_rest_password	-	None	N/A
hitachi_gad_rest_password_path	-	None	N/A
hitachi_gad_rest_user	-	None	N/A
hitachi_gad_thin_pool	-	None	N/A
hitachi_gad_ssl_cert_path	-	None	N/A
hitachi_gad_ssl_cert_verify	-	False	N/A
hitachi_gad_status_check_long_interval	-	5	N/A
hitachi_gad_status_check_short_interval	-	600	N/A
hitachi_gad_status_check_timeout	-	86400	N/A
hitachi_gad_storage_id	-	None	None
hitachi_gad_target_ports	-	[]	N/A
hitachi_gad_use_chap_auth	-	False	N/A
hitachi_gad_quorum_disk_id	-	None	N/A

hitachi_gad_copy_speed	-	3	N/A
hitachi_replication_journal_creation_speed	-	L	N/A
hitachi_replication_journal_overflow_tolerance	-	60	N/A
hitachi_replication_journal_path_failure_tolerance	-	5	N/A
hitachi_replication_journal_size	-	None	N/A
hitachi_replication_journal_transfer_speed	-	256	N/A
hitachi_replication_journal_use_cache	-	True	N/A
hitachi_replication_mun	-	1	N/A
hitachi_replication_path_group_id	-	0	N/A
hitachi_replication_status_check_long_interval	-	5	N/A
hitachi_replication_status_check_short_interval	-	600	N/A
hitachi_replication_status_check_timeout	-	86400	N/A
hitachi_gad_set_gad_reserve_attribute	-	True	N/A
hitachi_shared_targets	-	True	N/A
hitachi_debug_level	-	info	N/A

Legend:

- - : the feature is not supported
- N/A : the parameter is not supported and the value is not used

Known issue in migrating

Using Hitachi Storage Advisor Embedded as REST API server

Intree driver does not support Hitachi Storage Advisor Embedded as REST API server. If your system which uses Hitachi Storage Advisor Embedded as REST API server has any attached volumes, detach volumes and remove servers on your storage before updating your system to RHOSP16.2.

Note:

- If the parameter `hitachi_storage_cli=SIMPLE_REST` is set in the `cinder.conf`, your system uses Hitachi Storage Advisor Embedded as REST API server.

1. Add the parameter `hitachi_server_delete=True` to the section for the target backend in `cinder.conf`
2. Restart the cinder driver service by the following command:

```
# pcs resource restart openstack-cinder-volume
```

3. Run the following command for all volumes in all servers to detach volumes and remove servers.

```
# nova volume-detach <ID of instance> <ID of volume>
```

4. Verify all servers are removed.

Confirm the IP address and WWN of the Compute Node and Controller Node, respectively.

```
# ip address  
# systool -v -c fc_host
```

Verify any servers with the following names in the server list are not existed:

- HBSD-<WWN>
- HBSD-<IP address>

The following command is a sample for getting server list on raidcom:

```
# raidcom get server
```

The following command is a sample for removing the server on raidcom:

```
# raidcom delete server -server_id <ID of server> -request_id auto
```

Operation for migration

Backing up configuration files

Configuration files for Cinder, Nova and other OpenStack components will be initialized when updating your system. Before updating, back up the following files which you fixed after over-cloud deploy:

- On Controller Node

- o /var/lib/config-data/puppet-generated/cinder/*
- o /var/lib/config-data/puppet-generated/nova/*
- o /var/lib/config-data/puppet-generated/glance_api/*
- On Compute Node
 - o /var/lib/config-data/puppet-generated/nova_libvirt/*

Updating RHOSP

Update your RHOSP environment along [Keeping Red Hat OpenStack Platform Updated](#), which is provided by Red Hat.

Installing Driver

Installing intree driver

When updating your system to RHOSP 16.2, RHOSP 16.2 intree driver will be also installed.

Installing out of tree driver

If required, install manually out of tree driver which is not a container after updating to RHOSP16.2. See the following procedure:

1. On the controller node, create a new directory .
2. Transfer the HBSD media file to the newly created directory.
3. Extract the HBSD media.

```
# tar zxvf RHOSP16_2_HBSD_patch.tar.gz
__init__.py
hbsd_common.py
hbsd_fc.py
hbsd_iscsi.py
hbsd_replication.py
hbsd_rest.py
hbsd_rest_api.py
hbsd_rest_fc.py
hbsd_rest_iscsi.py
hbsd_utils.py
```

4. Created the following directory and copy the extracted files to the directory.

```
/var/lib/config-data/puppet-generated/cinder/usr/lib/python3.6/site-
packages/cinder/volume/drivers/hitachi
```

5. Check the attributes of the files.

```
owner: root
group: root
permission: -rw-r--r--
```

6. Restart the Cinder Volume Container.
7. Check if the status of the Cinder Volume Container is "started".

```
# pcs resource status
```

8. Check if the State of the Cinder Volume backend is "up" and the Backend State of the Cinder Volume backend is "up".

```
# cinder service-list
```

Fixing configuration files

Set the contents of the backed up configuration file to the upgraded configuration file , then, replace driver name and parameter names in cinder.conf as follows. Details of differences are in the description of the section "Overview of differences in Cinder driver".

- Required fields to replace in cinder.conf :
 - Driver name
 - For Fibre Channel, from
"cinder.volume.drivers.hitachi.hbsd.hbsd_fc.HBSDFCDriver" to
"cinder.volume.drivers.hitachi.hbsd_fc.HBSDFCDriver"
 - For iSCSI, from
"cinder.volume.drivers.hitachi.hbsd.hbsd_iscsi.HBSDISCSIDriver" to
"cinder.volume.drivers.hitachi.hbsd_iscsi.HBSDISCSIDriver"
 - Parameter names
 - from "hitachi_rest_user" to "san_login"
 - from "hitachi_rest_password" to "san_password"
 - from "hitachi_rest_api_ip" to "san_ip"

Note:

- Add the parameter "san_api_port=23451" to sections for each backends, if you use Configuration Manager REST API server.
- Recommend to add debug=True. The parameter will help

Migrating Driver

No operation is needed for data migration. Volumes and other data are migrated automatically when updating RHOSP.

Operation differences after migration

- LDEV number assigned to cinder volume
On out of tree driver, LDEV number which is assigned to cinder volume is saved as volume metadata. On intree driver, the way to get LDEV number is changed. Run the following command on the Controller node.

```
# podman exec galera-bundle-podman-0 mysql -c cinder -e "select provider_location from volumes where id=\"<VOLUME_ID>\";"
```

Note:

- Although volume metadata in migrated volume still has LDEV number, the LDEV number is not guaranteed.
- Intree driver records all messages to `/var/log/containers/cinder/cinder-volume.log`. `/var/log/containers/cinder/hbsd_debug.log` is not used.

Restrictions

Not applicable

Known Issues

1. GAD volume, which is created by out of tree driver before updating RHOSP, will fail removing, extending, migrating or failover. To solve the problem, update with fixed driver. Schedule for providing fixed driver is TBD.
2. If Remote Replication volume, which is created by out of tree driver before updating RHOSP, is exist, GAD volume can not be created on updated RHOSP environment. To avoid this case, remove all Remote Replication volumes before updating. To solve the problem, update with fixed driver. Schedule for providing fixed driver is TBD.
3. When the Cinder volume backend is down, Cinder scheduler is also down unexpectedly. When backend is down, restart the cinder scheduler service.

Hitachi Vantara

Corporate Headquarters 2535 Augustine Drive
Santa Clara, CA 95054 USA www.HitachiVantara.com community.HitachiVantara.com

Regional Contact Information

Americas: +1 866 374 5822 or info@hitachivantara.com

Europe, Middle East and Africa: +44 (0) 1753 618000 or info.emea@hitachivantara.com

Asia Pacific: +852 3189 7900 or info.marketing.apac@hitachivantara.com

